



CBA 3G-100 **800 MHz TO 3.1 GHz 100 WATT** **CLASS A BROADBAND AMPLIFIER**




- **Class A linear and low distortion design**
- **High reliability gallium arsenide technology**
- **Mismatch tolerant and unconditionally stable**
- **Wide instantaneous bandwidth**
- **Three year parts and labour warranty**

Designed specifically for Radiated EMC testing, this mismatch tolerant Class A amplifier delivers power continuously into the poor and variable match typically associated with testing above 1 GHz. Although antennas are usually well matched at these high frequencies, the presence of the EUT in the path of the antenna causes high levels of reflected power which only full Class A amplifiers can tolerate.

Whilst antenna gain is relatively constant, increasing cable losses at the higher frequencies demand increasing power with increasing frequency. Teseq amplifiers are therefore designed to maintain their high linear output power right up to and beyond the defined frequency range.

The GaAs Class A design ensures a high reliability, low distortion linear performance across the frequency range. This design also ensures that the amplifier will continue to operate at full power even when presented with an open or short circuit at its output.

The unit is powered from a switched mode power supply for high efficiency, high power factor and wide voltage range operation. The unit is air-cooled with integral fans, and is protected against faulty cooling by excess temperature sensing. A safety interlock connector is provided, which the user can short circuit to ground, to put the amplifier into standby mode. Front panel indicators are provided to indicate over-temperature and rf interlock condition.



CBA 3G-100

800 MHz TO 3.1 GHz 100 WATT CLASS A BROADBAND AMPLIFIER

Key RF Parameters

Frequency range (instantaneous)	800 to 3100 MHz
Rated output power	100 W minimum (110 W typical) 800 MHz to 3 GHz 90 W minimum (100 W typical) 3.0 GHz to 3.1 GHz
Output power at 1 dB gain compression	90 W minimum (100 W typical) 800 MHz to 3 GHz 80 W minimum (90 W typical) 3.0 GHz to 3.1 GHz
Harmonics at 90 W output (800 MHz to 3 GHz)	Better than -20 dBC
Gain	51 dB
Gain variation with frequency	±3 dB
Maximum input power (no damage)	+10 dBm

Impedance / VSWR

Output VSWR tolerance ¹	Infinite any phase
Stability	Unconditional
Output impedance	50 Ohms
Input VSWR	2:1

Additional RF Data

Third order intercept point ²	60 dBm
RF connector style	Type N female

Electrical and Interfaces

USB interface	Optional
Safety interlock	BNC female, s/c to mute
Supply voltage (single phase)	90 to 264 Vac
Supply frequency range	47 to 63 Hz
Supply power	<1 kVA

Physical / Environmental

Case dimensions	19 inch, 6U case, 550 mm deep
Weight	35 kg
Operating temperature range	0 to 40°C

Teseq AG
Nordstrasse 11F 4542 Luterbach Switzerland
T +41 32 681 40 40 F +41 32 681 40 48
sales@teseq.com www.teseq.com

© September 2013 Teseq®
Specifications subject to change without notice.
Teseq® is an ISO-registered company. Its products
are designed and manufactured under the strict
quality and environmental requirements of the ISO
9001. This document has been carefully checked.
However, Teseq® does not assume any liability for
errors or inaccuracies.

Notes:

1. Output VSWR tolerance is specified for excitation within the permitted levels and frequency range.
2. The third order intercept point is a nominal value, as its calculation depends upon the power level at which distortion measurements are made.